

Hot Air Sterilizing Drying Oven

Characteristics:

- Horizontal air circularly by double Air ducts, high efficiency and high uniformity.
- PID controller, with over-temperature protection function.
- New anti-hot handle.
- LCD temperature controller.
- 4 grades speed fan, adjustable for different requirements.
- Over-temperature protection system.
- High precision digital independent temperature limiter.



Main Technical Parameters:

Model		TLS-30	TLS-45	TLS-65	TLS-85	TLS-125	TLS-230
Function	CycleMode	Forced convection					
	Temp. Range	RT+10-300°C					
	Temp. Resolution Ratio	0.1°C					
	Temp. Motion	±1°C					
	Temp. Uniformity	±2.5%					
Structure	Inner Chamber	SUS304					
	Outer Shell	SUS304					
	Insulation Layer	High quality rockwool board (with CE)					
	Heater	stainless steel heater					
	Power Rating	0.8kW	1.2kW	1.6kW	2.0kW	2.3kW	3.0kW
Controller	Exhaust Hole	φ35mm top (with function of test hole)					Rear exhaust
	Temp. Control Mode	Two temperature section PID intelligent					
	Temp. Setting Mode	Touch button setting					
	Temp. Display Mode	LCD Digital display					
	Timer	0-9999min(with timing wait function)					
	Operation Function	Fixed temperature operation, fixed timing operation, auto stop.					
	Additional Function	Sensor deviation correction, temperature overshoot self-tuning, internal parameter locking, power-off parameter memory					
	Sensor	PT100					
Specification	Safety Device	Digital Independent Temp. limiter, Over temperature sound-light alarm.					
	Inner Chamber Size(W*L*H)(mm)	310*310*310	350*350*350	400*360*450	450*420*450	500*450*550	600*500*750
	Exterior Size (W*L*H)(mm)	460*510*695	500*550*735	550*550*840	590*610*830	636*680*915	735*835*1115
	Packing Size (W*L*H)(mm)	540*575*855	580*615*895	635*625*995	680*685*1000	710*730*1100	857*885*1287
	Volume	30L	45L	65L	85L	125L	230L
	Max. Shelf Number	5	6	8	8	11	17
	Load Per rack	15kg					
	Shelf Space	40mm					
	Power Rating (50/60HZ)	AC220V/3.6A	AC220V/5.5A	AC220V/7.2A	AC220V/9.0A	AC220V/10.5A	AC220V/13.6A
	NW/GW(kg)	33/37	37/43	44/49	50/56	60/66	94/120
Accessory	Shelf	2					
	Shelf Frame	4					
Optional accessories		Spares shelf, RS485 interface, printer, Program controller, U-disk storage, 4.3-inch color touch screen temperature controller.					