

	64 Import Procedures (Type P)	17MF-2P	17MF-4P	17MF-8P	17MF-12P	17MF-20P	17MF-36P
	30 Section 7.0-inch Touch Screen (Model With PL)	17MF-2PL	17MF-4PL	17MF-8PL	17MF-12PL	TX4-20-17PL	TX 4-36-17PL
<b>Function</b>	Temp Range	Max 1700°C(Long-term maximum continuous operating temperature 1650°C)					
	Temp Accuracy	±1°C					
	Temp Resolution Ratio	1°C					
	Temperature Rise Time	≤140 min					
<b>Structure</b>	Variable Hearth Volume	High temperature resistant polycrystalline mullite fibre					
	Exterior	Cold-rolled steel plate, surface spray treatment					
	Chamber Size	150*90*150	150*150*150	300*150*150	300*200*200	300*260*260	300*400*300
	Exhaust Hole	Outer Diameterφ22, Inner Diameter18					
	Heater	High temperature resistant silicon molybdenum rod					
	Heating Power	3kW	5.5kW	6kW	10kW	12kW	15kW
<b>Controller</b>	Temp Control	P-type: LCD display controller PL type: 7.0 inch touch screen program temperature control, with curve view, U disk data storage function					
	Temperature Control Mode	Intelligent microcomputer PID control					
	Setting Method	P type: 5 key Settings Type PL: touch operation					
	Timer	No letter model: 0-9999 minutes Type P: 0-99 hours 59 minutes PL type: 0-9999 minutes					
	Operation Function	Fixed value running or program running					
	Sensor	Type B thermocouple					
	Additional Function	Heating start and stop button, sensor fault alarm, temperature overshoot self-setting, temperature correction Type PL has U disk data storage function					
	Safety Device	Over temperature alarm, leakage protection, door off heating					
	Exterior Size(W*L*H mm)	600*755*1100	600*815*1100	750*815*1100	750*865*1150	750*925*1210	750*1065*1250
	Packing Size(W*L*H mm)	760*925*1310	760*985*1310	910*985*1310	910*1045*1360	910*1105*1420	910*1265*1460
	Inner Volume	2L	3.4L	6.7L	12L	20L	36L
	Power Supply (50/60 Hz) Rated Current	AC220V50Hz			AC380V/50Hz		
	NW/GW(kg)	70/90	80/100	110/130	150/170	175/195	270/320
<b>Addable configuration</b>	Charging port						