

Model		TLO-30	TLO-45	TLO-65	TLO-85	TLO-125	TLO-230
Cycle Mode		Forced convection					
Function	Temp. Range	RT+10-300℃					
	Temp. Resolution Ratio	0.1℃					
	Temp. Motion	±1℃					
	Temp. Uniformity	±2.5%					
Structure	Inner Chamber	Mirror Stainless Steel					
	Outer Shell	SUS304					
	Insulation layer	High quality rock wool board(with CE)					
	Heater	Stainless steel heater					
	Power Rating	0.8kW	1.2kW	1.6kW	2.0kW	2.3kW	3.0kW
	Exhaust Hole	Φ35mmtop(with function of test hole)					Rear exhaust
Controller	Temp. Control Mode	Two temperature section PID intelligent					
	Temp. Setting Mode	Touch button setting					
	Temp. Display Mode	Measuring temperature display on upper LCD screen,setting temperature display on the lower row					
	Timer	0-9999min(with timing wait function)					
	Operation Function	Fixed temperature operation, timing function, auto stop.					
	Additional Function	High precision digital independent temperature limiter, 4 grade 3 speed adjustable-speed fan (230 model without fan speed adjustor),sensor deviation correction, temperature overshoot self-tuning, internal parameter locking, power-off parameter memory					
	Sensor	PT100					
	Safety Device	Digital Independent Temp.limiter,Over temperature sound-light alarm.					
Specification	Inner Chamber Size(W*L*H)(mm)	310*310*310	350*350*350	400*360*450	450*420*450	500*450*550	600*500*750
	Exterior Size (W*L*H)(mm)	450*500*690	490*540*730	540*550*830	590*610*830	640*640*930	735*835*1115
	Packing Size (W*L*H)(mm)	540*575*855	580*615*895	635*625*995	680*685*1000	710*730*1100	857*885*1287
	Volume	30L	45L	65L	85L	125L	230L
	Max. Shelf Number	5	6	8	8	11	17
	Load Per rack	15kg					
	Shelf Space	40mm					35mm
	Power Rating (50/60HZ)	AC220V/3.6A	AC220V/5.5A	AC220V/7.2A	AC220V/9.0A	AC220V/10.5A	AC220V/13.6A
	NW/GW (kg)	33/37	37/43	44/49	50/56	60/66	94/120
Accessory	Shelf	2					
	Shelf Frame	4					
Optional Accessories		Spare Shelf, RS485 Interface, Printer, Program controller, U-disk storage; 3.5-inch color touch screen temperature controller					