

Model		TLO-25B
Cycle Mode		Forced convection
Function	Temp Range	RT+10-250°C
	Temp Resolution	0.1°C
	Temp Fluctuation	±1°C
	Temp Uniformity	±2.5%
Structure	Inner Chamber	High quality stainless steel plate
	Outer Shell	Cold rolling steel electrostatic spraying exterior
	Insulation Layer	High quality rock wool board(with CE)
	Heater	Stainless steel heater
	Power Rating	0.2kW
	Exhaust Hole	Φ32mm top (with function of test hole)
Controller	Temp Control Mode	Dual-temperature fuzzy PID
	Temp Setting Mode	Touch button setting
	Temp Display Mode	Measuring temperature,display on upper row;
		Setting temperature,LED digital display
	Timer	0-9999min(with timing wait function)
	Operation Function	Fixed temperature operation,timing function,auto stop
	Additional Function	Sensor deviation correction,temperature overshoot self-
	Sensor	pt100
Safety Device		Over temperature sound-light alarm
Specification	Inner chamber Size(W*L*H	300*320*270
	Exterior Size(W*L*H mm)	600*500*482
	Packing Size(W*L*H mm)	730*630*612
	Volume	25L
	Shelf Number	9
	Load Per Rack	15kg
	Shelf Space	25mm
	Current Rating(50/60HZ)	AC220V/0.9A
	NW/GW(kg)	15/20
Accessory	Shelf	2
	Shelf Frame	4
Optional Accessories		Shelves